Inpadoc/Fam.& Legal Stat (Dialog® File 345): (c) 2001 EPO. All rights reserved.

3. **2** 7/19/3 (Item 1 from file: 347)

05104394 RUBBER COMPOSITION FOR TIRE TREAD

Pub. No.: 08-059894 [**JP 8059894** A] **Published:** March 05, 1996 (19960305)

Inventor: OTA TOSHIYUKI

MATSUO KENJI
SAKIYAMA ATSUSHI
IWAFUNE SEIICHIRO

Applicant: BRIDGESTONE CORP [000527] (A Japanese Company or Corporation), JP (Japan)

Application No.: 06-195540 [JP 94195540]

Filed: August 19, 1994 (19940819)

International Class: [6] C08L-009/06; C08K-003/04; C08K-003/36; C08K-005/54; C08L-

057/02; C08L-061/14

JAPIO Class: 14.2 (ORGANIC CHEMISTRY -- High Polymer Molecular Compounds); 26.2

(TRANSPORTATION -- Motor Vehicles)

ABSTRACT

PURPOSE: To obtain a rubber composition which can give a tire tread improved in grip on a wet or semiwet road surface in both low-temperature and high- temperature regions without detriment to wear resistance.

CONSTITUTION: This composition comprises 100 pts.wt. rubber component containing at least 70 pts.wt. SBR of a styrene content of 20-60%, 5-150 pts.wt. powdery inorganic compound represented by the general formula, mM(sup 1).xSiOy.zH(sub 2)O (wherein M(sup 1) is at least one metal selected from among Al, Mg, Ti and Ca, oxides thereof, and hydroxide thereof; and (m), (x), (y) and (z) are integers of 1-5, 0-10, 2-5 and 0-10, respectively) and having a particle diameter of 0.01-10.mu.m, 5-150 pts.wt. silica having a nitrogen adsorption specific surface area of 130-280m(sup 2)/g, and 5-170 pts.wt. (the total amount of the inorganic compound, the silica and this component being 80-250 pts.wt.) carbon black having a nitrogen adsorption specific surface area of 80-288m(sup 2)/g and has a content of acetone/chloroform extractibles of 30-270 pts.wt. after vulcanization.

JAPIO (Dialog® File 347): (c) 2001 JPO & JAPIO. All rights reserved.



© 2001 The Dialog Corporation plc